

Amendments to the Claims:

Claims 1, 10 and 11 are cancelled and claims 2, 4 to 7 and 9 are amended as set forth hereinafter.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Cancelled).

2. (Currently Amended) A closed level control system for a vehicle having a vehicle body, vehicle axles and pressurized medium chambers with which the vehicle body is suspended relative to corresponding ones of said vehicle axles, the closed level control system comprising:

pressurized medium supply vessel means having first and second pressurized medium spaces for holding a medium under pressure as a pressurized medium;

said first and second pressurized medium spaces having no direct connection therebetween;

a compressor for transferring said pressurized medium between said pressurized medium supply vessel means and said pressurized medium chambers;

said compressor having an input and an output;

first and second controllable directional valves and each one of said valves having at least two switching states

comprising a first and a second switching state; and,

said first controllable directional valve being switchable to connect either said first pressurized medium space or said
20 second pressurized medium space to said compressor input or to said compressor output so that pressurized medium from said pressurized medium chambers can be transferred into said first pressurized medium space or into said second pressurized medium space or pressurized medium from said first pressurized medium
25 space or from said second pressurized medium space can be transferred to said pressurized medium chambers,

wherein said pressurized medium is pressurized air and said system further comprising comprises:

a first pressurized air line connecting said first
30 controllable directional valve to said input of said compressor;

a second pressurized air line connecting said output of said compressor to said second controllable directional valve;

a third pressurized air line connecting said input of said compressor to said second controllable directional valve;

35 a fourth pressurized air line connecting said output of said compressor to said first controllable directional valve;

said pressurized medium chambers being connected to said second controllable directional valve;

said first pressurized air line being switched through by
40 said first controllable directional valve in [[a]] said first switching state thereof and said second pressurized air line being switched through by said second controllable directional valve in [[a]] said first switching state thereof and said fourth pressurized air line being blocked by said first controllable

45 directional valve in said first switching state thereof and said
third pressurized air line being blocked by said second
controllable directional valve in said first switching state
thereof when pressurized air is transferred from one of said
first and second pressurized medium spaces into one of said
50 pressurized medium chambers;

said third pressurized ~~medium~~ air line being switched
through by said second controllable directional valve in [[a]]
said second switch switching state thereof and said ~~first~~ fourth
pressurized air line being switched through by said first
55 controllable directional valve in [[a]] said second switching
state thereof and said first pressurized air line being blocked
by said first controllable directional valve and said second
pressurized air line being blocked by said second controllable
directional valve in [[a]] said second switching state thereof
60 wherein pressurized air is transferred from one of said
pressurized medium chambers into one of said first and second
pressurized medium spaces;

a third controllable directional valve interposed between
said first controllable directional valve and said pressurized
65 medium spaces and said third controllable directional valve
likewise having at least two switching states comprising a first
and a second switching state;

said third controllable directional valve being switched
into [[a]] said first switching state thereof to provide a
70 connection from said first controllable directional valve to said
first pressurized medium space and to block a connection to said
second pressurized medium space; and,

said third controllable directional valve being switched into [[a]] said second switching state thereof to provide a
75 connection from said first controllable directional valve to said second pressurized medium space and to block a connection to said first pressurized medium space.

3. (Original) The closed level control system of claim 2, wherein said first pressurized air line and said third pressurized air line conjointly define a common connecting point; and, wherein said closed level control system further comprises:

5 a first check valve mounted in said first pressurized air line between said common connecting point and said first controllable directional valve and said first check valve being disposed so as to be open toward said input of said compressor; and,

10 a second check valve mounted in said third pressurized air line between said common connecting point and said second controllable directional valve and said second check valve being open toward said input of said compressor.

4. (Currently Amended) The closed level control system of ~~claim 1~~ claim 2, wherein said first and second pressurized medium spaces of said pressurized medium supply vessel means are separate first and second pressurized medium supply vessels.

5. (Currently Amended) The closed level control system of ~~claim 1~~ claim 2, wherein said first and second pressurized medium spaces have different pressure levels.

6. (Currently Amended) The closed level control system of ~~claim 1~~ claim 2, wherein the pressure in at least one of said first and second pressurized medium spaces is greater than the maximum actual compression end pressure of said compressor.

7. (Currently Amended) The closed level control system of ~~claim 1~~ claim 2, further comprising an additional air line connected into ~~[[a]]~~ one of said pressurized air ~~line~~ lines of said system to facilitate control of an external apparatus
5 utilizing the pressure in at least one of said first and second pressurized medium spaces; and, the residual pressure in the other one of said pressurized medium spaces being available to execute a level change of said level control system directly after an external control operations.

8. (Original) The closed level control system of claim 7, wherein said external apparatus is a tire inflating device.

9. (Currently Amended) The closed level control system of claim 2, further comprising:

an air dryer mounted in said fourth pressurized air line;

~~an intake valve switchable between a base position wherein
5 no throughflow is permitted and a switched position wherein
throughflow is permitted,~~

an air inlet/air outlet;

an intake line ending at said ~~intake valve~~ air inlet/air
outlet and connecting said input of said compressor to the
10 atmosphere ~~when said intake valve is in said switched position~~

via said air inlet/air outlet;

~~a discharge~~ an additional controllable directional valve
switchable between a base position wherein no throughflow is
permitted and a switched position wherein throughflow is
15 permitted to said air inlet/air outlet;

~~a discharge~~ said second pressurized line branching off from
said fourth pressurized air line at a branch point between said
output of said compressor and said air dryer and ending at said
~~discharge~~ additional controllable directional valve; and,
20 said pressurized medium supply vessel means being
connectable to the atmosphere via said air dryer and said
~~discharge~~ second pressurized line when said ~~discharge~~ additional
controllable directional valve is in said switched position
thereof.

Claims 10 and 11 (Cancelled).